Package: geocompkg (via r-universe)

Title Geocomputation with R Metapackage

Version 2.2.3

Description Package supporting the book Geocomputation with R
(\url{https://r.geocompx.org}). The packages in the Imports are
required to build the first chapter of the book. The packages
in Suggests are required for Part II and III.

Imports dplyr, sf, terra, spData, spDataLarge, units, methods

URL https://github.com/geocompx/geocompkg,
https://geocompx.github.io/geocompkg/

BugReports https://github.com/geocompx/geocompr/issues

RoxygenNote 7.2.3

Suggests bench, bookdown, bslib, cartogram, classInt, codetools,
data.table, dismo, downlit, exactextractr, future, gdalcubes,
geodata, geogrid, geosphere, GGally, ggplot2, ggspatial, gh,
gstat, historydata, htmlwidgets, httr, kableExtra, kernlab,
knitr, igraph, languageserver, leaflegend, leaflet, lgr,
link2GI, lwgeom, mapdeck, mapsf, mapview, magick, metathis,
mlr3, mlr3extralearners, mlr3learners, mlr3proba,
mlr3spatiotempcv, mlr3tuning, mlr3viz, miniUI, nabor, odbc,
openeo, osmdata, paradox, plotly, pool, pROC, progressr, purrr,
qgisprocess, ranger, rcartocolor, readr, reprex, rgrass,
rmapshaper, rmarkdown, rnaturalearth, rnaturalearthdata,
RPostgres, RPostgreSQL, Rsagacmd, rstac, s2, sfnetworks,
smoothr, stars, stplanr, stringr, tibble, tictoc, tidygeocoder,
tidytext, tidyr, tmap, tmaptools, tree, vegan, covr

Remotes mlr-org/mlr3extralearners, mlr-org/mlr3proba,
nowosad/spDataLarge, r-tmap/tmap

VignetteBuilder knitr

Encoding UTF-8

License CC BY-NC-ND 4.0

Repository https://geocompr.r-universe.dev

RemoteUrl https://github.com/geocompr/geocompkg

RemoteRef HEAD

RemoteSha e6c5d110632fbdaf150f27ba667ea2e460308409

Contents

---

add_impact   *Return details of issues, with input an GitHub issue URL*

Description

Return details of issues, with input an GitHub issue URL

Usage

```
add_impact(
  url_issue,
  vars = c("created_at", "type", "title", "comments", "state", "creator"),
  url_old_impact = NULL
)
```

Arguments

url_issue   The url of the issue to add

vars   Which variables to use?

url_old_impact The previous state of the 'impact.csv' file

Examples

```
## Not run:
url_issue = "https://github.com/mtennekes/tmap/issues/196"
geocompr:::add_impact(url_issue)
u = "https://github.com/Robinlovelace/geocompr/raw/main/our-impact.csv"
geocompr:::add_impact(url_issue, url_old_impact = u)

## End(Not run)
```

Index